

ECOFINISH PLUS

Ready-to-use water-based emulsion paint remover for high-quality exposed finishes



[info. PRECAUTIONS]

Use according to the instructions on the technical and safety data sheet. Wear full protective clothing. Consult the toxicological data sheet in accordance with EU Regulation 2015/830. Substances in the Candidate List (Art. 59 REACH); based on the data, the product does not contain SVHC substances $\geq 0.1\%$.

[info. CONSUMPTION]

Approximately 25 g/m² of surface area.

[info. PACKAGING]

- 1050 L tank
- 210 L drum
- 25 L canister

[info. STORAGE]

The product is sensitive to frost, therefore storage at temperatures between +5 °C and 40 °C is recommended. At temperatures equal to or below 2 °C, separation of the emulsion may occur. Maximum storage: 6 months in original, unopened packaging.

[info. TECHNICAL SERVICE]

Detailed technical instructions on the use of the products can be requested from your local representative or directly from PROIND S.r.l.

ECOFINISH PLUS is a **reverse emulsion form release agent, formulated with special synthetic oils and biodegradable additives of plant origin, free from toxic or harmful substances for operators and the environment.**

ECOFINISH PLUS guarantees an excellent finish for exposed concrete structures, reducing (even with minimal product use) the formation of macro and micro bubbles and ensuring perfectly uniform surfaces.

Thanks to the use of special inhibitors, it keeps formwork clean and protects it from corrosion. The product is also suitable for delayed demoulding.

Fields of application

ECOFINISH PLUS can be used in all sectors where effective formwork release is required for concrete works or structures. It is therefore suitable for both heavy and light prefabrication and for shipbuilding, in all applications where concrete surfaces of a high aesthetic standard are required.

In the prefabrication sector, the product is suitable for both natural curing and steam curing.

ECOFINISH PLUS is compatible with all types of formwork: metal, treated wood and plastic formwork (polystyrene, rubber, polyurethane, etc.). It is also particularly recommended for applications on vertical surfaces.

Instructions for use and consumption

Apply ECOFINISH PLUS to formwork using sprayers equipped with comb nozzles, with operating pressures above 4 atm, or with a brush. It is recommended to use small quantities of product: approximately 20-25 g/m² covers 1 m² of surface area; in the presence of absorbent formwork, consumption can reach up to 30 g/m². The best formwork removal results are generally obtained after 5-10 uses of the same formwork.

Do not apply ECOFINISH PLUS on surfaces with temperatures above 40 °C. Before application, the formwork must be clean and dry: the presence of water or concrete residues prevents the formation of the thin protective film and compromises the formwork removal action.

Before pouring the concrete, wait for the water component of the product to evaporate and for a continuous oily film to form on the surface.

Equipment

We provide specialised equipment for quick and extremely economical application of our form release agents. We recommend using the STAR 25 pump. Our Technical Department is available to assess the equipment and methods of use best suited to your needs.