

RAPIDSFORM BIO

Environmentally friendly quick-release disarming device



[info. PRECAUTIONS]

Use in accordance with the instructions on the health and safety data sheet in compliance with EU Regulation 2020/878. The product does not contain any hazard warnings. Wear full protective clothing. Substances on the Candidate List (Art. 59 REACH): absent

[info. CONSUMPTION]

Approximately 1 L / 60 m² of surface area.

[info. PACKAGING]

- Bulk in tank
- 1050 L tank
- 210 L drum
- 25 L canister
- 10 L canister

[info. STORAGE]

The product can be stored for long periods in its original packaging without undergoing any changes. It is sensitive to frost: if stored outdoors during the winter, it may freeze. If the product is partially crystallised, homogenise it with a mechanical agitator before use.

[info. TECHNICAL SERVICE]

Detailed technical instructions on the use of the products can be requested from your local representative or directly from PROIND S.r.l.

RAPIDSFORM BIO is a **ready-to-use, environmentally friendly release agent that isolates the formwork from the concrete through physical-mechanical action and reacts chemically with the concrete to create an insulating element in the form of a thin film with no actual cohesion, which provides the most effective separation between the concrete and the formwork.** It gives the moulded surfaces a uniform appearance with sharp edges.

Fields of application

RAPIDSFORM BIO is a release agent suitable for any type of concrete poured into metal formwork. It is not recommended for use on polystyrene formwork or other plastic materials. The product is particularly suitable for the immediate release of kerbs, blocks, pipes, manholes and similar structures.

Instructions for use and consumption

Apply a very thin layer of the product to the formwork using sprayers with suitable nozzles, or spread with a slightly dampened pad. Avoid excessive application: quantities greater than necessary may compromise the appearance of the product. One litre of RAPIDSFORM BIO can treat approximately 60 m² of surface area.

Equipment

We have developed special equipment for the rapid and extremely economical application of our formwork release agents. Our Technical Department is at your disposal to identify the solution that best suits your needs.