

# ALCHIOIL 200

Universal chemical-physical action disarming agent with medium viscosity and high anti-corrosive power



---

## [ info. PRECAUTIONS ]

---

Use according to the instructions on the technical and safety data sheet. Wear full protective clothing. Consult the toxicological data sheet in accordance with EU Regulation 2015/830. Substances in the Candidate List (Art. 59 REACH): based on the data, the product does not contain SVHC substances  $\geq 0.1\%$ .

---

## [ info. CONSUMPTION ]

---

Approximately 1 L / 50 m<sup>2</sup> of surface area.

---

## [ info. PACKAGING ]

---

- In bulk
- 1050 L tank
- 210 L drum
- 25 L tank
- 10 L container

---

## [ info. STORAGE ]

---

The product can be stored for a long time in its original packaging without any changes.

---

## [ info. TECHNICAL SERVICE ]

---

Detailed technical instructions on the use of the products can be requested from your local representative or directly from PROIND S.r.l.

ALCHIOIL 200 is a latest-generation disarming agent.

It contains special additives with high anti-corrosive power that act as inhibitors, **preventing the formation of rust stains on metal formwork.**

### Fields of application

ALCHIOIL 200 provides exceptional release between formwork and concrete, while protecting the formwork from oxidation, which is so common with normal release agents. ALCHIOIL 200 contains a balanced blend of additives that allow it to be used for both horizontal and vertical casting, while providing effective protection against rust.

ALCHIOIL 200 is particularly suitable for castings that must undergo forced curing, although its versatility means it can be defined as a universal release agent.

ALCHIOIL 200 does not emit unpleasant odours and the additives used are even used in cosmetics, protecting and safeguarding the health of users.

### Instructions for use and consumption

Spray a very thin layer of the product onto the formwork using appropriate sprayers and nozzles, or wipe it on with a slightly damp cloth. One litre of ALCHIOIL 200 is sufficient to treat approximately 50 m<sup>2</sup> of surface area.

### Equipment

We have developed special equipment for the quick and extremely economical application of our release agents. Our Technical Department is available to assess the equipment best suited to your needs.