

ALCHIOIL 400

Universal, ultra-low viscosity release agent for demoulding concrete products



[info. **PRECAUTIONS**]

Use in accordance with the instructions on the technical data sheet and safety data sheet. Wear full protective clothing. Consult the toxicological data sheet.

[info. **CONSUMPTION**]

Approximately 1 L / 50 m² of surface area.

[info. **PACKAGING**]

- In bulk
- 1050 L tank
- 210 L drum
- 25 L tank

[info. **STORAGE**]

The product must be kept away from open flames or sources of heat.

[info. **TECHNICAL SERVICE**]

Detailed technical instructions on the use of the products can be requested from your local representative or directly from PROIND S.r.l.

ALCHIOIL 400 is a **particularly fluid release agent** specially formulated with special substances that allow easy and effective demoulding of products, which will have an excellent visible finish.

Fields of application

ALCHIOIL 400 has been specially formulated for medium-speed demoulding of small and medium-sized items and is suitable for steel, wood or concrete formwork.

ALCHIOIL 400 is a ready-to-use release agent: spray application is recommended, although it can also be applied using traditional methods with a brush or paintbrush.

ALCHIOIL 400 can also be applied at very low temperatures and does not alter the visible surface of concrete, on which it does not create any problems for the application of water-based paints or plasters.

Instructions for use and consumption

Apply a very thin layer of ALCHIOIL 400 to the formwork. Do not apply the product to formwork at very high temperatures (60 °C). One litre of ALCHIOIL 400 can treat an average of approximately 50 m² of surface area. ALCHIOIL 400 should not be used on surfaces with temperatures above 40 °C.

Equipment

We have developed special equipment for the quick and extremely economical application of our release agents. Our Technical Department is available to assess the equipment best suited to your needs.