

Ready-to-use water-based emulsion paint remover for high-quality exposed finishes



[info. **PRECAUTIONS**]

- Avoid freezing.
- Shake well before use.
- Use in accordance with the instructions on the technical data sheet and safety data sheet. Wear full protective clothing. Consult the toxicological data sheet.
- Sostanze in Candidate List (Art.59 REACH): in base ai dati il prodotto non contiene sostanze SVHC $\geq 0,1\%$.

[info. **CONSUMPTION**]

Approximately 1 L / 80 m² of surface area.

[info. **PACKAGING**]

- 1050 L tank
- 210 L drum
- 25 L tank

[info. **STORAGE**]

The product is sensitive to frost, therefore it is advisable to store it at temperatures between +5°C and 40°C.

Maximum storage: 6 months in original, unopened packaging.

[info. **TECHNICAL SERVICE**]

Detailed technical instructions on the use of the products can be requested from your local representative or directly from PROIND S.r.l.

ECOFINISH is a form release agent **formulated with special synthetic oils and biodegradable plant-based additives**, free from substances that are toxic or harmful to operators and the environment.

ECOFINISH guarantees an excellent finish for exposed concrete structures, reducing the formation of macro and micro bubbles with very modest product usage, making the surfaces of the structures perfectly uniform. Thanks to the use of special inhibitors, ECOFINISH keeps formwork clean, protecting it from corrosion. Also suitable for delayed demoulding.

Fields of application

ECOFINISH can be used on smooth or rough formwork made of steel, plywood or polyester, to remove any type of concrete, except for concrete with a moist earth consistency.

ECOFINISH is also recommended for vertical surfaces.

Instructions for use and consumption

Spray ECOFINISH onto the formwork using sprayers and comb nozzles at operating pressures above 4 atm. It is recommended to apply a modest amount of product, bearing in mind that 1 litre of ECOFINISH can treat approximately 80 m² of surface area. ECOFINISH should not be used on surfaces with temperatures above 40 °C.

Equipment

We provide specialised equipment for quick and extremely economical application of our form release agents.

We recommend using the STAR 25 pump. Our Technical Department is available to assess the equipment and methods of use best suited to your needs.