

NUOVO DISARMOIL

Water-emulsifiable dismoulding agent for wooden formwork



[info. **PRECAUTIONS**]

Use in accordance with the instructions on the technical data sheet and safety data sheet. Wear full protective clothing. Consult the toxicological data sheet.

[info. **CONSUMPTION**]

Approximately 1 L / 100 m² of surface area.

[info. **DOSAGE**]

1 L of NUOVO DISARMOIL in approximately 20 parts water.

[info. **PACKAGING**]

- In bulk
- 1050 L tank
- 210 L drum
- 25 L tank
- 10 L container

[info. **STORAGE**]

The product can be stored for a long time in its original packaging without alteration.

[info. **TECHNICAL SERVICE**]

Detailed technical instructions on the use of the products can be requested from your local representative or directly from PROIND S.r.l.

NUOVO DISARMOIL is a **latest-generation degreaser, formulated with special synthetic oils and emulsifiers of the highest quality, free from SVHC substances**. It comes in the form of a straw-coloured oily liquid which, once mixed with water, provides excellent protection for wooden or plywood formwork, helping to maintain its durability and integrity over time.

Fields of application

NUOVO DISARMOIL is particularly suitable for use on wooden or plywood formwork to obtain concrete with an excellent exposed finish. NUOVO DISARMOIL should be diluted in the recommended proportions, taking care not to use water that is too cold and always pouring the oil into the water and not vice versa.

Instructions for use and consumption

NUOVO DISARMOIL should be diluted in water at a ratio of 1 part product to 15-20 parts water. Before application, it is advisable to remove any residues or fragments of hardened concrete from the formwork. One litre of suitably diluted product can treat approximately 100 m² of surface area, depending on the condition of the wood used.

Advantages

NEW DISARMOIL guarantees the durability and protection of wooden formwork and does not alter the original colour of the product.

Equipment

We have developed special equipment for the rapid and extremely economical application of our formwork release agents. Our Technical Department is at your disposal to identify the solution that best suits your needs.