

VIBROFORM SF

Disarming for quick removal



[info. **PRECAUTIONS**]

Use in accordance with the instructions on the technical data sheet and safety data sheet. Wear full protective clothing. Consult the toxicological data sheet.

[info. **CONSUMPTION**]

Approximately 1 L / 80 m² of surface area.

[info. **DOSAGE**]

1 L / 80 m² of surface area.

[info. **PACKAGING**]

- 1050 L tank
- 210 L drum
- 25 L tank

[info. **STORAGE**]

The product can be stored for long periods in its original packaging in a covered location. Keep the product away from sources of heat.

[info. **TECHNICAL SERVICE**]

Detailed technical instructions on the use of the products can be requested from your local representative or directly from PROIND S.r.l.

VIBROFORM SF is a ready-to-use release agent specially formulated for the **rapid demoulding of concrete products**.

The high degree of lubricity of the product allows for perfect cleaning of the moulds and an excellent finish on the surfaces of the concrete products. VIBROFORM SF is a transparent liquid.

Fields of application

VIBROFORM SF is suitable for all types of instant demoulding of manufactured items, for concrete casting in metal formwork intended for the production of small and medium-sized manufactured items.

Instructions for use and consumption

VIBROFORM SF is used as is and can be applied by spray or brush.

Under normal conditions, 1 litre of VIBROFORM SF can cover approximately 80 m² of surface area.

Equipment

We have developed special equipment for the rapid and extremely economical application of our formwork release agents. Our Technical Department is at your disposal to identify the solution that best suits your needs.